# WARISAN GEMILANG FAST CREW BOAT & UTILITY VESSEL



# EASTMAL MARITIM SERVICES SDN. BHD.

No. 43, Lot 2396, Lorong Bakti 1B1, PJ Heights, Jalan Sultan Tengah, Petrajaya, 93050 Kuching, Sarawak



## PRINCIPAL PARTICULARS

Port Of Registry : Port Kelang
Call Sign : 9MID8
IMO No. : 9529384
Official No. : 333969
Year Built : 2008

Class : Bureau Veritas (BV)

Notation : 1<sup>™</sup> Hull <sup>™</sup> Mach Crew boat ; Special service –

Utility vessel, Coastal Area
Type : Fast Crew Boat /Utility Vessel

Flag : Malaysia

Operator : GOF Offshore Sdn Bhd

#### **DIMENSION**

Length Overall : 34.00 m Length Registered : 31,49 m Breadth Moulded : 7.83 m Depth Moulded 3.30 m **Draft Moulded** : 1.50 m Summer freeboard : 1.735 m **GRT** : 226 mt **NRT** : 67 mt Deadweight : 44 mt

## PERFORMANCE

Speed : 25.0 knots

Type of fuel : Marine Gas Oil (MGO)

#### **CARGO CAPACITIES**

Deck Cargo : +/-20 mt
Deck Strength : 2.5 Ton/m²

Clear Deck Area : 65.10 m² (6.2m x 10.5m)

 Fuel Oil
 : 50 m³

 Fresh Water
 : 20 m³

 Sludge Tank
 : 250 ltrs

 Dispersant tank
 : 200 ltrs

 Cargo railing height
 : 1.118m

# PROPULSION SYSTEM

Main Engine : 3 x 1450 BHP @ 2300 rpm Caterpillar C32

Main Generator : 2 x 75 kW Cummins 6BT5.9 DM

Bow Thruster : 1 x 1 Ton Thrust

Steering Gear : 1 x Kobelt 7175 MA (electrohydraulic)
Propulsion : 3 x 5 Bladed FPP of Nickel Aluminum Bronze

Rudders : 2 nos

## **DECK EQUIPMENT**

Anchor Winch : Electrical, single drum and warping head

1 ton nominal pull at 9m/min

Anchors : High Holding Power type, 1 x 135kg (approx.)
Chains : Steel wire rope (length and breaking strength as

required by Class) c/w 12.5m x 14mm dia. stud

link chain

Bollards : 4 x 100mm dia. double-bit / 2 x 100mm dia. single

bit

Mooring Chocks : 4

### FIRE FIGHITING EQUIPMENT

#### **External**

Fire monitor : 2 units fitted on the port and starboard side aft

(stern) on the main deck.

Fire pump : 323m³/hr (Volvo Penta – Standalone unit)

#### Internal

Fixed System in E/R : CO<sub>2</sub> System

Fire Detection System : Fire Alarm Panel Notifier

Emergency Fire Pump : Diesel driven 30m³/hr portable type Fireman's outfit : 2 units complete with breathing device

Fire blanket : 3 nos.

#### NAVIGATIONAL /COMMUNICATION EQUIPMENTS

GMDSS : 1 set T&T SSB : 1 set Sailor

SART : 2 x ACR PATHFINDER TM

EPIRB : 1 set Kannad Auto

Inmarsat C : 1 set T&T VHF Radio : 2 x T&T

Portable VHF Radio: 3 x handheld VHF, 2.5W, I.S. type c/w spare

battery & charger

Navtex Receiver : 1 x McMurdo, ICS NAV 5 PLUS

X-Band Radar : 1 x Furuno Echo Sounder : 1 x Skipper, ED165

GPS : 1 x Koden Electronics
Gyro compass : 1 x Anschutz
Autopilot : 1 x SIMRAD AP50
Speed Log : 1 x Anthea
Magnetic Compass : 1 set c/w reflector

AIS : 1 x Furuno

## ACCOMMODATIONS

Berths : 8 berths for marine officer/crew

Hospital : 1 berths
Passenger Seating : 50 persons
\*All cabins are fully air-conditioned

## LIFE SAVING APPLIANCE

Search Lights : 2 x 1000W

Liferafts : 6 x 25 Men SOLAS Type

Lifebuoys : 8 pcs Life jackets : 90 pcs Work Vest : 8 units EEBD : 2 units

Line Throwing : 4 projectiles and lines

Apparatus

Scrambling net : 2 units (4m x 3m)

Rescue boat : 1 inflatable rescue boat for 6 men with 25HP

outboard motor & launching davit

## **AUXILLIARY SYSTEM**

Rescue Zone : Port & Starboard at Main deck Oily Water Separator : 1 nos. of 0.5t/hr Georim

Particulars given are entirely without warranty as to correctness and interested parties must satisfy themselves by inspection of the vessel Revision as at 10<sup>th</sup> September 2016.